



NOTES:

THE EXACT NUMBER, LOCATION, AND SPACING OF ALL SIGNS SHALL BE ADJUSTED TO FIT FIELD CONDITIONS.

IF THERE ARE EXISTING ROUTE MARKER ASSEMBLIES THAT WILL REMAIN IN PLACE, ADJUST THE LOCATION OF THE DETOUR SIGNS TO CORRESPOND WITH THE EXISTING ASSEMBLIES.

THE SPACING BETWEEN THE TRAFFIC CONTROL AND DETOUR SIGNS SHOULD BE ADJUSTED NOT TO CONFLICT WITH AND TO PROVIDE A MINIMUM OF 200' CLEARANCE TO EXISTING SIGNS THAT WILL REMAIN IN PLACE.

ANY SIGNS, TEMPORARY OR EXISTING, WHICH CONFLICT WITH TRAFFIC CONTROL "IN USE", SHALL BE REMOVED OR COVERED AS NEEDED AND AS APPROVED BY THE ENGINEER AND PAID FOR UNDER THE ITEM TRAFFIC CONTROL COVERING SIGNS.

FOLLOW SDD "BARRICADES AND SIGNS FOR MAINLINE CLOSURES" FOR MAINLINE ROAD CLOSED SIGNAGE.

PLACE PCMS SIGNS AS IDENTIFIED IN PLANS. 10 DAYS IN ADVANCE OF PROJECT CONSTRUCTION. PCMS SIGNS WILL BE PAID FOR AS LUMP SUM ITEM. IT IS ESTIMATED UP TO 4 PCMS SIGNS MAY BE IN PLACE AT A GIVEN TIME.